

CEILING LOUDSPEAKER

Quam C10X/BU/WS/VC

C10X/BU/WS/VC consists of an 8" O.D., dual cone loudspeaker with a 10 oz. magnet and a 5W, 25/70V, multi-tap transformer. It includes a screwdriver or detachable knob (knob included) adjusted volume control and a round, stud-mount baffle with a white, powder coat finish.



APPLICATION	Intended Use: Program Material:	Indoor environment Signal tones, voice and music
AUDIO PERFORMANCE	Average Sensitivity: Loudspeaker Power Rating: Maximum Power Rating: Calculated Output: Magnet Type & Weight: Frequency Response: Nominal Coverage Angle: Audio Connection:	95 dB SPL, 1W/1M 20W RMS, EIA 426A Standard 15W @ 8 Ohms 102dB SPL, 5W/1M BeFe Ceramic, 10 oz. Nominal 65Hz - 17 kHz, EIA 426A Standard 100° Included Angle, -6dB/2kHz, Half space 7", Color-coded, Pre-tinned Leads
COMPONENT	Dimensions: Combined Weight: Loudspeaker Model: Loudspeaker Specs: Transformer: Baffle: Finish:	12 7/8" (Diameter) x 2 1/2" (D) 4.2 lbs. 8C10PAX 8" O.D. loudspeaker, 10 oz. magnet TBLU: 5W, 25/70V, with 5 taps (0.31W, 0.63W, 1.25W, 2.5W, 5.0W) BR8WS: round, steel, stud-mount White powder coat finish
RECOMMENDED QUAM COMPONENTS	Enclosures: Mounting Supports:	ERD-8, ERD8U SSB-2, SSB-3, SSB-7

